

Identification of Preparation & Company

Product Name: Stipple Coat
Application: Application: Roller
Intended Use: An exterior coating for plywood, brick, masonry
Company Identification: Britmet Tileform Limited Unit 8, Coneygree Industrial Estate,
Coneygre Road Tipton, West Midlands DY4 8XP
Telephone: 0121 522 2709

Composition and Ingredient Information

Water-based dispersion of organic and inorganic pigments in a mixture of styrene acrylic resin etc.

Hazards Identification

This product is not classified as a hazardous dry film state or liquid on available data. However, repeated skin contact can cause dermatitis in sensitive individuals. Eye contact may irritate.

First Measures:

Skin Contact: wash with water before the paint dries. Remove contaminated clothing.

Eye contact: wash with plenty of water for several minutes and seek medical advice if irritation persists.

Ingestion: give plenty of water and seek medical advice. Do not introduce vomiting.

Fire Fighting Measures

Adequate dispersions will not burn. Dried films are combustible. Water, foam, carbon dioxide or dry powder extinguishers are all suitable.

Accidental Release Measures

Spillage should not be allowed to enter drains, and should be soaked up with sand or sawdust. It can then be disposed of as low hazard waste.

Handling and Storage

Handling: Avoid prolonged contact with skin

Storage: Store in closed containers and protect from frost.

Exposure Controls and Personal Protection

No OEL values are applicable, however, local exhaust ventilation may be required if the product is sprayed.

Physical and Chemical Properties

Physical state: Liquid
Odour: slight ammonia ester
Flashpoint: N/A
Water solubility: miscible in water

Stability and Reactivity

Stable under normal conditions of use.

Toxicological Information

Long-term experience of handling this class of product under normal conditions indicates the absence of any chronic or acute effects.

Ecological Information

No data is available on the product itself. However, if admitted into waterways the product is miscible and will be progressively diluted. Polymer and other solids will be largely absorbed into the sludge and consequently removed from the wastewater.

Disposal Considerations

Do not empty into drains or watercourses. Waste should be disposed of in accordance with regulations of the Control of Pollution Act and the Environmental Act.

Transport Information

Britmet Tileform coatings are not classified as hazardous for transportation.

Regulatory Information

This product is classified and labelled for supply in accordance with the chemicals (Hazard information and packaging) regulations:

R phrases: None

S phrases: None

The Control of Substances Hazardous to Health (COSHH) regulations apply to the use of this product.